

UNO-2053GL

AMD Geode™ GX Automation Computer
with 2 x LAN, 2 x COM, Audio, PC Card



Features

- Onboard AMD Geode GX533 (400 MHz) CPU
- Two standard RS-232 and one DB-15 VGA connector
- Two 10/100Base-T RJ-45 ports
- Two USB and one type I/II PC card slot
- Audio with Mic in, Line in, Line out
- Windows® CE 5.0 & 6.0, Windows XP Embedded SP2, and Linux ready solution
- Fanless design with no internal cabling
- Isolation between chassis and power ground

Introduction

The UNO-2053GL is a X86-grade platform that offers dual LAN and dual USB interfaces to fulfill user's diverse communication needs. In addition, it also offers two RS-232 communication ports on board. Therefore, UNO-2053GL is an ideal solution for data gateway applications. UNO-2053GL is available with a pre-configured Windows CE image with optimized onboard device drivers. Microsoft Windows CE is a compact, highly efficient, real-time operating system designed for embedded systems without mechanical HDD limitations. To expand storage capability, the UNO-2053GL allows the addition of an external 2.5" HDD using Advantech's UNO HDD expansion kit. It can be used for large data backup requirements and popular OS installations such as Microsoft Windows and Linux OS. Significant anti-vibration is maintained even with the mechanical HDD inside.

The UNO-2053GL is a perfect embedded application-ready platform that can shorten your development time and offer a rich networking interface to fulfill diverse requirements.

Specifications

General

- **Certification** CE, FCC class A, UL, CCC
- **Dimensions (W x D x H)** 188.8 x 106.5 x 35.5 mm (7.5" x 4.2" x 1.4")
- **Enclosure** Aluminum
- **Mounting** Wallmount, DIN-rail
- **Industrial** Grounding Isolation between chassis and power ground
- **Power Consumption** 15 W (Typical)
- **Power Requirements** 9 ~ 36 V_{DC} (e.g. +24 V @ 1 A) (Min. 24 W), AT
- **Weight** 0.8 kg
- **OS Support** WES Windows XP Embedded, Windows 2000 & XP, Windows CE 5.0 & 6.0, Linux
- **System Design** Fanless with no internal cabling
- **Remote Management** Built-in Advantech DiagAnywhere agent on Windows CE / XPe

System Hardware

- **CPU** LX800 500MHz
- **Memory** Onboard 256 MB DDR SDRAM
- **Indicators** LEDs for power, IDE and LAN (Active, Status)
- **Keyboard/Mouse** 1 x PS/2
- **Storage** SSD: 1 x internal type I/II CompactFlash® slot
HDD: expansion kit for 2.5" IDE HDD (Option)
- **Display** DB15 VGA connector, 1024 x 768 @ 60 Hz
- **Audio** Mic in, Line in, Line out
- **Watchdog Timer** Programmable 256 levels timer interval, from 1 to 255 sec

I/O Interface

- **LAN** 2 x 10/100Base-T RJ-45 ports
- **Serial Ports** 2 x standard RS-232
- **Serial Port Speed** RS-232: 50 ~ 115.2 kbps
- **USB Ports** 2 x USB ports, EHCI. Rev. 2.0 compliant

Environment

- **Humidity** 95 % @ 40°C (non-condensing)
- **Ingress Protection** IP40
- **Operating Temperature** (IEC 60068-2-2, 100% CPU/ I/O loading)
-10 ~ 55°C (14 ~ 131°F)
- **Shock Protection** IEC 68 2-27
CompactFlash®: 20 G @ DIN, half sine, 11 ms,
50 G @ Wall/Panel, half sine, 11 ms
- **Vibration Protection** IEC 68 2-6
CompactFlash: 2 Grms @ sine, 5 ~ 500 Hz,
10 ct./min, 1hr/axis
HDD: 1 Grms @ sine, 12 ~ 300 Hz, 10 ct./min, 1hr/axis

Ordering Information

- **UNO-2053GL-G30E** LX800 500MHz, 256 MB RAM Automation Computer

Accessories

- **UNO-HD20-AE** UNO-2000 HDD expansion kit
- **UNO-FPM21-AE** UNO-2000 series VESA mount kit
- **PCLS-DIAGAW10** Advantech Remote Monitoring & Diagnosis Utility