

ESP-9112

High Performance 10/40GbE Top of Rack Network Services Switch

NEW



Features

Hardware

- Built-in Freescale™ T4240 QorIQ Communication Processor with three DDR3 RDIMMs
- Broadcom StrataXGS® Trident II BCM56854 switch solution
- 680Gbps forwarding bandwidth
- Supports 6x QSFP and 44x SFP+
- Redundant & Hot-swappable DC PSU design
- Four redundant hot-swappable fan modules
- Rear-to-front cooling
- Supports Solid State Drive or Hard Disk Drive
- Network boot nodes from the switch
- IPMI 2.0 compliant hardware management function
- Open IPMI compliant hardware management function

Introduction

The ESP-9112 is a new generation of switch from Advantech Networks and Communications Group and is optimized for use in software-defined networks (SDN) requiring 10 and 40 Gigabit Ethernet connectivity. It combines a high performance, low-latency Broadcom StrataXGS® Trident II BCM56854 switch for up to 680Gbps of forwarding bandwidth and a server-class Freescale QorIQ T4240 communication processor with 24-cores, providing a powerful and flexible platform that supports enhanced features essential for top-of-the-rack deployment in modern data center switching installations. Data center networks require increasingly denser 10GbE and 40GbE connectivity at the access and aggregation layers in order to address the higher speed network interface cards being deployed in servers and the increased link utilization due to widespread use of virtualization. The ESP-9112 combines the performance and efficiency of a traditional network switch with the manageability, flexibility and security required for SDN.

With fiber support for six 40GbE QSFP ports and forty-four 10GbE SFP+ ports in a 1U rackmount design, the ESP-9112 can be used to build highly scalable, feature-rich, top-of-rack switches and aggregation equipment to connect big data, cloud and optimized workloads in the data center. When enabled by VortiQa Open Network switch software, Enterprise IT and cloud service providers will be able to drive greater flexibility and efficiency into their software defined infrastructure to support the increasing demand for new and innovative services. The platform utilizes standards-based protocols such as OpenFlow, and supports manageability through open technologies such as OpenStack and OpenDaylight. It also enables exceptional network security for virtualized environments by supporting the integration of high performance packet processing functions such as firewalling, intrusion detection and IPSEC over VxLAN. It also includes VNF support, commercial grade VortiQa SDN software supporting OpenFlow version 1.3 with extensions for Layer 4 and above protocols, and Layer 2/3 forwarding.

Redundant, hot swappable, DC power supplies and fans, along with IPMI 2.0 and OpenIPMI hardware management interfaces provide the high availability and management features which equip the switch for managing business-critical traffic. One 10/100/1000 Ethernet RJ45 port and two serial ports are available for out-of-band management with two USB ports available for installation and maintenance needs. One ID LED helps users identify fail equipment in short time. Two 128GB SSD devices within the chassis provide storage for boot images allowing external network nodes to be loaded and booted from the switch.

Specifications

Hardware

Processor, Memory and Switch	Processor	Freescale™ T4240 QorIQ 1.6GHz Communication Processor
	Flash Memory	2 x 1Gbit SPI Flash
	Max DDR3 DIMM#	3 x (16GB RDIMM)
	Ethernet Switch	Broadcom StrataXGS® Trident-II BCM56854
	Forwarding Bandwidth	680Gbps
Ethernet I/O (on rear side)	Fiber Version	44 x 10GbE ZSFP+ 6 x 40GbE QSFP
	Ethernet	3 x GbE RJ-45
Management I/O	Serial	1 x RJ-45 Type console port for T4240 QorIQ
	USB	2 x USB
	SATA	2 x SATA devices (128GB SSD)
System FRU	Power supply	2 x Redundant DC PSU
	Power input	AC 100 -240 V @ 47-63 Hz, full range
	Type/Watt	500 W 2U (1+1 redundant, 500 W each)
	System power consumption	370 Watt Average
	System Fans	4 x Hot-swappable redundant FAN trays
Physical	Dimension (W x D x H)	431.8 x 558.8 x 43.2 mm (17" x 22" x 1.7")
	Weight	18 kg
Environment	Operating	0 to 40° C @ 1800m and 85%RH
	Storage	- 20 to 70° C @ 3000m and 95%RH

Ordering Information

Part Number	Description
ESP-9112-F2AP0E	ESP-9112 fiber version with Broadcom SDK. 44 ports 10GbE ZSFP+, 6 ports 40GbE QSFP, Freescale™ T4240 QorIQ 1.6GHz Communication Processor and 16 GB DDR3-1333 MHz memory & 256 GB SSD

Please contact your Advantech regional sales office or email ncg@advantech.com for additional ordering information and pricing.